

WYSE
| | | |

THE GLOBAL LEADER IN
CLOUD CLIENT COMPUTING

Wyse® T class™

New standards for entry level thin clients.



Wyse T class: **All you need to know. Here.**



Introducing the Wyse T class

The new standard for entry level

Great to use. Great to manage.

Users will enjoy its vibrant multimedia and Flash that plays in VDI and its advanced local browser. It's easy to live with too, as the T50 is powered by Wyse-enhanced Linux featuring a simple user interface and a brisk 20 second "plug and display" start up. The T50 is an RDP 7 compatible client (unique for entry level clients) and is an ideal platform that's certified for Citrix Online Plugin 11.x Client with HDX – and VMware View Open Client – and provides support for Wyse TCX and VDA. Managers will especially welcome the T50's auto configuration and management as featured elsewhere in Wyse's premium thin and zero clients.



Start

Models

Features

Technical

Contact

Print

Features Wyse T class

The best user experience. On a budget.

New Wyse T50 is a compact affordable and flexible entry level thin client. It delivers the best Web, Citrix, Microsoft and VMware VDI user experience and performance to IT executives needing to equip their task workers with an enterprise standard client on a budget. Wyse T50 does this by featuring technology found across the premium range of Wyse cloud clients.

Performance



Connectivity



Mounting options



Green



Thin client Management



User Experience Optimization



User Experience Acceleration



Take a tour of the
Wyse T class range



Start

Models

Features

Technical

Contact

Print

Performance thin client

No compromise performance boost

At the heart of the new Wyse T50 beats the very latest Marvell ARM v6/v7 1.0 GHz processor delivering 150% better performance than the older 1.2GHz technology, over remote protocols like RDP. Coupled with its built in hardware media processor the T50 delivers smooth multimedia, bi-directional audio and Flash playback performance.

**ARM
v6|v7**

Processor

Wyse T class features an ARM v6/v7 1.0 GHz processor and is ready to work in under 20 seconds.



Continue tour



Start

Models

Features

Technical

Contact

Print

wyse.com

Connectivity

Wyse T class standard configuration, connects right out of the box

Unlike other entry level budget clients, the Wyse T50 arrives ready to connect to a huge array of environments including web based applications and services. It works seamlessly within Citrix, Microsoft and VMware environments and features the advanced Chromium web browser. Users can enjoy two monitors using the DVI-I display option and high speed networking with support for Gigabit Ethernet and optional integrated b/g/n WiFi.



Front of device

SD card slot

2 USB 2.0 ports

Output: 1/8-inch mini jack

Input: 1/8-inch mini jack,
8 bit stereo microphone

Optional 802.11
b/g/n Wireless

2 USB 2.0 ports

DVI-I port

RJ45 (10/100/1000Mbps)
network port

Kensington
lock slot



Continue tour



Start

Models

Features

Technical

Contact

Print

Mounting options

The Wyse T class family can be placed horizontally or vertically (with optional feet) on desktops, mounted to walls and even behind monitors.

Horizontal

Included stand allows the Wyse T class to be used horizontally.



Back of monitor or wall mounting

The included horizontal stand enables mounting to the rear of a monitor (this requires the four industry standard mounting points to be free). The same bracket can be used for wall mounting.



Vertical

Wyse T class clients are available with optional feet for vertical use.



Continue tour



Start

Models

Features

Technical

Contact

Print

Green computing without compromise



EarthSmart Computing™



That's Wyse EarthSmart™ computing

Saves budget. Saves the environment too.

New Wyse T50 delivers great value from day one and will keep on doing so with a lower TCO than other solutions. All while delivering vital green credentials with its ENERGY STAR Version 5.0 and EPEAT compliance.

Green Power

Wyse has implemented an ISO 14001-based environmental management system and WEEE recycling processes, and all Wyse products meet stringent ROHS requirements.

Learn more

Download carbon calculators, fact sheets and white papers from here:

www.wyse.com/green

Continue tour



Start

Models

Features

Technical

Contact

Print

wyse.com

Thin Client Management Wyse Device Manager

Wyse Device Manager (WDM) addresses key management requirements for deploying powerful thin clients. With its centralized management and administration WDM helps IT departments deliver more effective remote thin client support while minimizing end user downtime.

Security is assured with HTTPS based imaging, updates and downloads.

WDM delivers organization-wide benefits:

Operations	Centralized management. Collect and organize asset information.
Administration	Health status reports. Automated client settings. Update client firmware and add applications.
End User IT Costs	Easier more effective remote support. Create custom scripts and packages.
Minimize downtime	Restart or reset thin clients in less than a minute. Enforce policies. Minimize user errors.

At a glance features.

Security	HTTPS Based Imaging / Updates Fully Encrypted Network Traffic Delegated Admin Access (MS AD) Support
No-Hassle Deployment	Complete Device Imaging / Patching / Updates Bandwidth Throttling for Efficiency / Reliability Software Updates and Add-ons
Device Administration and Monitoring	Device Health Status / Reporting Remote Shadowing / Control Default Device Configuration
Reduce End User IT Costs	Reduce energy consumption with scheduled up/down times
Scalability	Distributed Architecture Microsoft SQL Database Support Multiple Remote Repository Support
Complete Asset Visibility	Automated device discovery Detailed Hardware Asset information Installed Software Asset information

Wyse
WDM™

Continue tour



Start

Models

Features

Technical


Contact

Print

User Experience Optimization Wyse TCX™ Suite with Collaborative Processing Architecture™


Wyse TCX delivers an amazing user experience in one software suite.

Wyse TCX Suite of virtualization software enriches the user experience by removing the limitations previously associated with thin clients. It enhances, not replaces, key protocols like ICA/HDX and RDP by adding key features to make each more valuable.



Multi-display


Ensures application windows and dialog boxes are multi-monitor aware when using more than one monitor.



USB Virtualization

Enables plug and play peripheral support for virtual desktop environments.


- Redirect and use local USB devices in virtual desktops.
- Deploy virtual desktops to knowledge workers with special device access needs.
- Enable a broad set of USB peripherals including webcams and headsets.



Multimedia acceleration

Streamlines the delivery of video and audio content to the local client for a rich user experience within a thin client computing architecture.

- Accelerates Mpeg1, Mpeg2, WMV, Mpeg4 Part 2, AC3, AAC, MP3, WAV, WMA media types.
- Collaborative Processing Architecture enhances server scalability, and network utilization by off-loading multimedia rendering to the client.



Flash acceleration

Flash acceleration helps thin client users to experience improved Flash video performance. While the Flash player continues to run server-side, the resulting images are transcoded and redirected to the client for fast rendering. The technology allows for greater control of frame rate and compression and supports enhanced playback of YouTube-style flash videos in Internet Explorer.



Bi-directional sound

Enables bi-directional audio in virtual desktop environments, enabling solutions such as VOIP, digital dictation or voice recognition to be deployed.

Continue tour



Start

Models

Features

Technical

Contact

Print

Virtualization Software Wyse Virtual Desktop Accelerator

Removing the barriers of network latency

Wyse Virtual Desktop Accelerator (VDA) enables virtualized desktop and thin computing environments to be deployed to areas where network latency has, to date, presented operational barriers. Now, with Wyse VDA, more users can receive the full benefits of Wyse thin computing – with the best PC experience over virtualized desktops.

Wyse VDA is a software-only solution for Wyse thin clients and supported PCs that delivers the best user experience for the allocated network bandwidth by neutralizing the effects of network latency and packet loss. Making ‘thin’ suitable for more remote-site, branch, or field-based users.

Wyse VDA works with instead of replacing existing RDP and ICA protocols, accelerating them by up to 20 times on networks faced with latencies up to and beyond 300ms, and at least 768kbps bandwidth.

At a glance features.

- Software-only acceleration of virtual desktops and applications
- Accelerates existing Citrix ICA and Microsoft RDP protocols
- Works on WANs and ‘fat, long pipes’
- Accelerates connections to Citrix XenApp, Citrix XenDesktop, VMware View and Microsoft Terminal Server and Microsoft Hyper-V VDI
- Enhances Wyse TCX software suite functionality across wide-area networks
- Enables Wyse Collaborative Processing Architecture across wide-area networks
- Administrator console provides control of maximum bandwidth per connection
- Leverages built-in security of underlying protocols (128-bit encryption for RDP and ICA).



Continue tour



Start

Models

Features

Technical

Contact

Print

Technical Wyse T class specifications

The Wyse T class is configured to work with Wyse Enhanced Ubuntu™ Linux operating systems.

Want to learn more? Simply click the relevant icon.

Wyse T class specifications



Wyse Enhanced Ubuntu™ Linux



Start

Models

Features

Technical

Contact

Print

Specifications

Wyse T50 thin client

Processors	Marvell ARM v6/v7 1.0 GHz processor
Memory	1GB Flash / 1GB RAM
I/O peripheral support	Four USB 2.0 One DVI-I port, DVI to VGA (DB-15) adapter included Dual display support with optional DVI-I to DVI-D plus VGA-monitor splitter cable (sold separately) SD Card Slot Enhanced USB Keyboard with Windows Keys (104 keys) and PS2 mouse port PS/2 Optical mouse included
Multimedia decoding	H.264, WMV9/VC1 Up to 720p local browser Flash support
Networking	RJ45 (10/100/1000Mbps) Factory options: Optional 802.11 b/g/n wireless support: WPA Personal, WPA2 Personal, WPA Enterprise, WPA2 Enterprise, WPA Enterprise Authentication support.
Display	Single: Up To 1920x1200@24bpp Dual: Up To 1920x1080@24bpp
Audio	Output: 1/8-inch mini jack Input: 1/8-inch mini jack, 8 bit stereo microphone
Mountings	Stand for horizontal use and VESAWall mounting (included) or vertical feet (optional)

Device Security	Built-in Kensington security slot (cable sold separately)
Physical characteristics	Height: 1 inch (25mm) Width: 6.9 inches (177mm) Depth: 4.69 inches (119mm)
Shipping Weight	1.003 lbs (.455kg)
Power	Worldwide auto-sensing 100-240 VAC, 50/60 Hz. Energy Star V5.0 Phase V external and EuP compliant power adapter Average power usage with device connected to 1 keyboard with 1 PS/2 mouse and 1 monitor: Under 7.2 watts
Temperature Range	Operating: 32° to 104° F (10° to 40° C), horizontal and vertical positions Storage : 14° to 140° F (-10° to 60° C)
Humidity	20% to 80% condensing 10% to 95% non-condensing
Safety Certifications	German EKHITB 2000, ISO 9241-3/-8 cULus 60950, TÜV-GS, EN 60950 FCC Class B, CE, VCCI, C-Tick WEEE, RoHS Compliant Energy Star & EPEAT compliant
Warranty	Three-year hardware warranty

[Start](#)[Models](#)[Features](#)[Technical](#)[Contact](#)[Print](#)

Software specifications

Wyse Enhanced-Linux

Firmware features	Wyse Enhanced Ubuntu* Linux Automatic Central Configuration Automatic Upgrades (FTP, HTTP, HTTPS) Secure, read-only file system with lockdown abilities Wyse RDP client (RDP7 Compatible) Citrix Online Plugin 11.x client (ICA 11.x) w/ HDX Mediastream, Plug-n-Play, Realtime, etc. VMware View Open Client compatible with View 4.5 (RDP) Web-based applications (Chromium browser, Flash, etc) SSH
Server OS Infrastructure Support	Citrix XenApp / Citrix Presentation Server Citrix XenDesktop VMware View Microsoft Windows Terminal Server 2003 & 2008
Keyboard language support	100+ Keyboard Layouts supported locally (English, German, Spanish, French, Italian, Dutch, Chinese, Japanese, Turkish)
Management	Automatic, "hands-off" configuration and upgrading of thin clients without the need for device management software. Optionally, administrators can choose to integrate with Wyse Device Manager (WDM) for more hands-on control: <ul style="list-style-type: none">- Complete image upgrade- Wake terminal remotely (Wake-on LAN)- Remote screen shadowing of entire desktop (VNC)- Asset management and reporting

Wireless support	WPA Personal, WPA2 Personal, WPA Enterprise WPA Enterprise Authentication support PEAP/TLS: PAP/MSCHAP/MSCHAPV2 support
Wyse TCX Suite	Advanced support for innovative Wyse TCX Suite virtualization software that both works with and enhances ICA and RDP (instead of replacing them) featuring: <ul style="list-style-type: none">- Multimedia acceleration - the power to run rich multimedia files formats utilizing Wyse Collaborative Processing Architecture (CPA) that intelligently redirects the necessary processing tasks between the thin client and the server.- Multi-display - ensures that windows and dialogue boxes behave the way users expect when using more than one monitor.- USB Virtualization - makes thin client-attached USB devices visible to virtual desktops and applications, with full IT control.- Bi-directional sound - enables virtual desktops and applications to receive and transmit high quality audio without compromise.- Flash acceleration - helps users of thin clients to experience improved Flash performance.
Wyse Virtual Desktop Accelerator	Neutralizes the effects of network latency and packet loss, making 'thin' more suitable for more remote-site, branch, or field-based users by boosting RDP and ICA up to 20 times on networks with latencies up to and exceeding 300ms and at least 768kbps bandwidth.

* Ubuntu™ is a registered trade mark of Canonical Group Limited



Start

Models

Features

Technical

Contact

Print

Contact Wyse

Wyse Technology Inc.

3471 North First Street,
San Jose, CA 95134-1801

Visit our website at:

<http://www.wyse.com>
or send an email to: sales@wyse.com

Wyse Sales

800 GET WYSE (800 438 9973)

International customers please dial:

00 1 408 473 1200

Wyse Support Portal

Wyse Support Portal provides a fast and accurate way to communicate interactively with Wyse Customer Support, and helps us respond to your requests more quickly.

<http://support.wyse.com/selfservice.html>

Wyse offers cloud client computing sales, service and support expertise around the globe. Click for contact details.



©2011 The Wyse logo and Wyse are trademarks of Wyse Technology Inc. Other product names mentioned herein are for identification purposes only and may be trademarks and/or registered trademarks of their respective companies. All specifications are subject to change without notice. Whilst we make every effort to ensure the accuracy of the details, specifications, models, images and benefits featured in this datasheet, we cannot be held responsible for any errors and/or omissions. If you have any queries regarding Wyse products please contact your authorized regional Wyse Partner or representative for further information and assistance. Some features require support by server operating system and protocol. Approved final 090511.

WYSE
| | | |
**THE GLOBAL LEADER IN
CLOUD CLIENT COMPUTING**
wyse.com



Start

Models

Features

Technical

Contact

Print

Wyse® T50

New standards for entry level thin clients.

WYSE

THE GLOBAL LEADER IN
CLOUD CLIENT COMPUTING

The best user experience. On a budget.

New Wyse T50 is a compact affordable and flexible entry level thin client. It delivers the best Web, Citrix, Microsoft and VMware VDI user experience and performance to IT executives needing to equip their task workers with an enterprise standard client on a budget. Wyse T50 does this by featuring technology found across the premium range of Wyse cloud clients.

Great to use. Great to manage.

Users will enjoy its vibrant multimedia and Flash that plays in VDI and its advanced local browser. It's easy to live with too, as the T50 is powered by Wyse-enhanced Linux featuring a simple user interface and a brisk 20 second "plug and display" start up. The T50 is an RDP 7 compatible client (unique for entry level clients) and is an ideal platform that's certified for Citrix Online Plugin 11.x Client with HDX – and VMware View Open Client – and provides support for Wyse TCX and VDA. Managers will especially welcome the T50's auto configuration and management as featured elsewhere in Wyse's premium thin and zero clients.

No compromise performance boost.

At the heart of the new Wyse T50 beats the very latest Marvell ARM v6/v7 1.0 GHz processor delivering 150% better performance than the older 1.2GHz technology, over remote protocols like RDP. Coupled with its built in hardware media processor the T50 delivers smooth multimedia, bi-directional audio and Flash playback performance.

Connects right out of the box.

Unlike other entry level budget clients, the Wyse T50 class arrives ready to connect to a huge array of environments including web based applications and services. It works seamlessly within Citrix, Microsoft and VMware environments and features the advanced Chromium web browser. Users can enjoy two monitors using the DVI-I display option and high speed networking with support for Gigabit Ethernet and optional integrated b/g/n WiFi.

Saves budget. Saves the environment too.

New Wyse T50 delivers great value from day one and will keep on doing so with a lower TCO than other solutions. All while delivering vital green credentials with its ENERGY STAR Version 5.0 and EPEAT compliance.

At a glance

Performance

Marvell ARM v6/v7 1.0 GHz processor delivering 150% better performance than older 1.2 GHz technology,

Operating systems

Wyse-enhanced Linux.

Connectivity

DVI-I interface with optional splitter cable enabling use of 2 monitors. Four USB 2.0 ports, Gigabit ethernet connectivity and optional WiFi 802.11 b/g/n support.

Management

Features Wyse auto-configuration and management software found on premium thin and zero clients. For customers that desire a little more hands-on approach (such as asset tracking, reporting, etc) then integration with Wyse Device Manager is built-in.

Multimedia performance

Hardware accelerated video decoding for smooth multimedia VC1/WMV9, and H.264 playback.

Green

Energy Star Version 5.0 and EPEAT compliance.



Call Wyse: 800 GET WYSE (800 438 9973)

wyse.com

Specifications

Wyse T50 thin client

Processors	Marvell ARM v6/v7 1.0 GHz processor
Memory	1GB Flash / 1GB RAM
I/O peripheral support	Four USB 2.0 One DVI-I port, DVI to VGA (DB-15) adapter included Dual display support with optional DVI-I to DVI-D plus VGA-monitor splitter cable (sold separately) SD Card Slot Enhanced USB Keyboard with Windows Keys (104 keys) and PS2 mouse port PS/2 Optical mouse included
Multimedia decoding	H.264, WMV9/VC1 Up to 720p local browser Flash support
Networking	RJ45 (10/100/1000Mbps) Factory options: Optional 802.11 b/g/n wireless support: WPA Personal, WPA2 Personal, WPA Enterprise, WPA2 Enterprise, WPA Enterprise Authentication support.
Display	Single: Up To 1920x1200@24bpp Dual: Up To 1920x1080@24bpp
Audio	Output: 1/8-inch mini jack Input: 1/8-inch mini jack, 8 bit stereo microphone
Mountings	Stand for horizontal use and VESA/Wall mounting (included) or vertical feet (optional)
Device Security	Built-in Kensington security slot (cable sold separately)
Physical characteristics	Height: 1 inch (25mm) Width: 6.9 inches (177mm) Depth: 4.69 inches (119mm)
Shipping Weight	1.003 lbs (.455kg)
Power	Worldwide auto-sensing 100-240 VAC, 50/60 Hz. Energy Star V5.0 Phase V external and EuP compliant power adapter Average power usage with device connected to 1 keyboard with 1 PS/2 mouse and 1 monitor: Under 7.2 watts
Temperature Range	Operating: 32° to 104° F (10° to 40° C), horizontal and vertical positions Storage : 14° to 140° F (-10° to 60° C)
Humidity	20% to 80% condensing 10% to 95% non-condensing
Safety Certifications	German EKI-ITB 2000, ISO 9241-3/-8 cULus 60950, TÜV-GS, EN 60950 FCC Class B, CE, VCCI, C-Tick WEEE, RoHS Compliant Energy Star & EPEAT compliant
Warranty	Three-year hardware warranty

Wyse Technology Inc.
3471 North First Street
San Jose, CA 95134-1801

Visit our website at:
<http://www.wyse.com>
Or send email to: sales@wyse.com

Wyse Sales
800 GET WYSE
(800 438 9973)

Wyse Support Portal:
A fast and accurate way to communicate
interactively with Wyse Customer Support.
<http://support.wyse.com/selfservice.html>

©2011 The Wyse logo and Wyse are trademarks of Wyse Technology Inc. Other product names mentioned herein are for identification purposes only and may be trademarks and/or registered trademarks of their respective companies. Specifications subject to change without notice. Some features require support by server operating system and protocol. Approved final 090511.

WYSE
THE GLOBAL LEADER IN
CLOUD CLIENT COMPUTING
wyse.com