Technical Specifications

Operating system: ThinLinux\SLED.

CPU: Quad-core AMD G-Series SoC 1.5 GHz.

Memory: 4GB Flash/ 2GB RAM(ThinLinux) 32GB Flash / 4GB RAM DDR3L (Windows 10 IoT Enterprise) 32GB Flash / 4GB RAM DDR3L (Windows Embedded 7P) 16GB Flash / 4GB RAM DDR3L (Windows Embedded 7) Optional SSD storage also supported Graphics AMD Radeon HD 8330E graphics (integrated with APU)

I/O peripheral support: 1 x DisplayPort. (Optional DisplayPort to DVI-I adapter available) 1 x One DVI-I port. DVI to VGA (DB-15) adapter included 4 x USB 2.0 ports (two front, two rear) 2 x SuperSpeed USB 3.0 ports on rear (backwards compatible with USB 2.0) Networking 10/100/1000 Gigabit Ethernet Optional dual band 802.11 a/b/g/n wireless with Bluetooth connectivity Resolution VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate DisplayPort: 2560 x 1600 at 32bpp / DVI-I: 1920 x 1200 at 32bpp Dual display: 1920 x 1200 at 32bpp / Supports dual digital high-resolution displays

Audio: Composite audio jack: 1/8-inch mini, 16-bit stereo / Internal mono speaker.

Dimensions: Height: 6.7 inches (170 mm) / Width: 1.6 inches (40 mm) / Depth: 7.3 inches (185 mm)

Weight: 2.05 lbs. (0.93 kg)

Mountings: Vertical feet, standard Optional VESA mounting bracket for mounting to flat surfaces, such as walls

Device security: Built-in Kensington security slot (cable sold separately)

Power: Worldwide auto-sensing 100-240 VAC, 50/60 Hz 65W, 19V DC Energy Star V.5.2 Phase V external and EuP compliant power adapter

Temperature range: Operating, vertical position: 32° to 104° F (10° to 40° C) Storage: 14° to 140° F (-10° to 60° C)

Humidity: 20% to 80% condensing. 10% to 95% non-condensing Safety certifications Ergonomics: German EKI-ITB 2000, ISO 9241-3/-8 Safety: cULus 60950, TÜV-GS, EN 60950 RF Interference: FCC Class B, CE, VCCI, C-Tick Environmental: WEEE, RoHS Compliant

Warranty: Three-year hardware warranty.

Support and deployment Complete services portfolio including Deployment Services, ProSupport and Accidental Damage service.

Compatibility

Horizon Clients - 4.7.0

- Partner Solution: Dell Wyse 5020(D50Q) thin client with Linux ThinLinux 1.0.7
- Third Party Solution: 5020(D50Q) ThinLinux 1.0.